

abstract

The obdgpslogger uses a sqlite database to store its recorded data. The schema is quite undocumented. I try to do this here on my own.

schema

<i>trip</i>	[table]
<i>tripid</i>	INTEGER
"start"	REAL
"end"	REAL

<i>obd</i>	[table]
load_pct	REAL
temp	REAL
rpm	REAL
vss	REAL
iat	REAL
maf	REAL
throttlepos	REAL
"time"	REAL

<i>gps</i>	[table]
lat	REAL
lon	REAL
alt	REAL
"time"	REAL

obdgpslogger sqlite schema
generated by SchemaCrawler 15.04.01
generated on 2019-03-07 09:50:02

As you can see here, there are no direct connections between the tables. Its quite flat. Therfor the logi is in the application (somehow).

Tables

trip

obd

Spalte	Beschreibung	unit
load_pct	Calculated LOAD Value	%
temp	Engine Coolant Temperature	Celsius
rpm	Engine RPM	rev/min (rpm)
vss	vehicle speed sensor	km/h
iat	Intake Air Temperature	Celsius
maf	mass air flow sensor	g/s
throttlepos	Absolute Throttle Position	%
time	??	??

gps

From:

<https://wiki.siningsoft.de/> -

Permanent link:

<https://wiki.siningsoft.de/doku.php?id=mycar:software:db&rev=1553980462>

Last update: **2019/03/30 21:14**

